


ADJ. ALUMINUM GANTRY CRANE WITH DUAL TIRE PNEUMATIC CASTERS - AHA-4-8-12-PNU

APPROX WEIGHT: 437.49 lbs.

(DOES NOT INCLUDE WEIGHT
OF POWER OR PACKAGING!!!)

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ***

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



3D VIEW

DIMENSION TOLERANCE $\pm 1/4"$

STANDARD FEATURES

MODEL NUMBER IS AHA-4-8-12-PNU
CAPACITY IS 4,000 LBS.

BASE WIDTH IS 73 1/16"
MAX OVERALL HEIGHT IS 164 1/8"

I-BEAM HEIGHT IS 8"

I-BEAM WIDTH IS 4"

OVERALL I-BEAM LENGTH IS 96"

USABLE I-BEAM LENGTH IS 72 1/4"
ADJUSTABLE UNDER I-BEAM HEIGHT

126 1/8" MIN

156 1/8" MAX

HEIGHT IS ADJUSTABLE IN 6" INCREMENTS

(4) $\phi 15 1/2"$ DUAL TIRE PNEUMATIC CASTERS
(SWIVEL WITH (4) LOCKING POSITIONS)

-PNU MODELS ARE 12" TALLER THAN STANDARD

AHA UNITS OF THE SAME HEIGHT DESIGNATION
ALUMINUM CONSTRUCTION

SPECIAL FEATURES

NONE

APPROVAL

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.
UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE
[] As drawn [] As marked

Signed: _____ Date: _____

Printed Name: _____

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING

DISTRIBUTOR'S NAME:		P.O.#
HOF EQUIPMENT COMPANY		X
PH: 888-990-1150		W.O.#
DRAWN BY: MTS		X
DATE: 01/29/2021		SALES: X
REFERENCE: X	SCALE: 1:44	FILE NAME:
QUOTED LEAD TIME: X	QUOTE # X	28-007-470


ADJ. ALUMINUM GANTRY CRANE WITH DUAL TIRE PNEUMATIC CASTERS - AHA-4-10-12-PNU

APPROX WEIGHT: 471.37 lbs.

(DOES NOT INCLUDE WEIGHT
OF POWER OR PACKAGING!!!)

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ***

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



STANDARD FEATURES

MODEL NUMBER IS AHA-4-10-12-PNU
CAPACITY IS 4,000 LBS.

BASE WIDTH IS 39 13/16"
MAX OVERALL HEIGHT IS 164 1/8"

I-BEAM HEIGHT IS 8"

I-BEAM WIDTH IS 4 3/16"

OVERALL I-BEAM LENGTH IS 120"

USABLE I-BEAM LENGTH IS 96 1/4"

ADJUSTABLE UNDER I-BEAM HEIGHT

126 1/8" MIN

156 1/8" MAX

HEIGHT IS ADJUSTABLE IN 6" INCREMENTS

(4) ϕ 15 1/2" DUAL TIRE PNEUMATIC CASTERS
(SWIVEL WITH (4) LOCKING POSITIONS)

-PNU MODELS ARE 12" TALLER THAN STANDARD

AHA UNITS OF THE SAME HEIGHT DESIGNATION
ALUMINUM CONSTRUCTION

SPECIAL FEATURES

NONE

APPROVAL

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS
REPRESENTED SATISFIES DESIGN AND DIMENSION
REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO
CONFIRM PRODUCT AND INSTALLATION
COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE
AND LOCAL REGULATIONS AND STANDARDS.
**UNITS REQUIRING APPROVAL DRAWINGS OR
MODIFIED ARE NON-RETURNABLE**
[] As drawn [] As marked

Signed: _____ Date: _____

Printed Name: _____

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING


DISTRIBUTOR'S NAME:		P.O.#
HOF EQUIPMENT COMPANY		X
PH: 888-990-1150		W.O.#
DRAWN BY: MTS		X
DATE: 01/29/2021		SALES:
REFERENCE: X		FILE NAME:
QUOTED LEAD TIME: X		28-007-461
QUOTE #		
X		

ADJ. ALUMINUM GANTRY CRANE WITH DUAL TIRE PNEUMATIC CASTERS - AHA-4-12-12-PNU

APPROX WEIGHT: 485.84 lbs.
(DOES NOT INCLUDE WEIGHT
OF POWER OR PACKAGING!!!)

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ***

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



STANDARD FEATURES

MODEL NUMBER IS AHA-4-12-12-PNU
CAPACITY IS 4,000 LBS.

BASE WIDTH IS 39 13/16"
MAX OVERALL HEIGHT IS 164 1/8"

I-BEAM HEIGHT IS 8"

I-BEAM WIDTH IS 4 3/16"

OVERALL I-BEAM LENGTH IS 144"

USABLE I-BEAM LENGTH IS 120 1/4"
ADJUSTABLE UNDER I-BEAM HEIGHT

126 1/8" MIN

156 1/8" MAX

HEIGHT IS ADJUSTABLE IN 6" INCREMENTS

(4) $\varnothing$ 15 1/2" DUAL TIRE PNEUMATIC CASTERS
(SWIVEL WITH (4) LOCKING POSITIONS)

-PNU MODELS ARE 12" TALLER THAN STANDARD

AHA UNITS OF THE SAME HEIGHT DESIGNATION
ALUMINUM CONSTRUCTION

SPECIAL FEATURES

NONE

APPROVAL

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.
UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE

[] As drawn [] As marked

Signed: _____ Date: _____

Printed Name: _____

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING

DISTRIBUTOR'S NAME:		P.O.#
HOF EQUIPMENT COMPANY		X
PH: 888-990-1150		W.O.#
DRAWN BY: MTS		X
DATE: 01/29/2021		SALES: X
REFERENCE: X	SCALE: 1:42	FILE NAME:
QUOTED LEAD TIME: X	QUOTE # X	28-007-464