CUSTOMER INFORMATION	HDD DRUM DUMPER
CONTACT:	
COMPANY:	SURVEY SHEET
PHONE:	
EMAIL:	
CONTAINER TYPE & SIZE HDD WORKS WITH STANDARD 55- AND 30-GALLON PLASTIC, STEEL, AND FIBER DRUMS. IF YOU WOULD LIKE TO DUMP A DIFFERENT CONTAINER, PLEASE SPECIFY SIZE: LENGTH: WIDTH:	ROTATED
HEIGHT: DIAMETER:	45° DUMP
IF YOU PLAN TO USE A DOLLY WITH YOUR DRUMS, PLEASE SPECIFY OVERALL SIZE OF DOLLY:	ANGLE
LENGTH: WIDTH:	
HEIGHT: DIAMETER:	
STANDARD FEATURES	
DESCRIPTION (CIRCLE ONE): PORTABLE STATIONARY	LEVEL
DUMP HEIGHT (CIRCLE ONE): 36" 48" 60" 72"	↑ HEIGHT
CAPACITY (CIRCLE ONE): 750 LBS. 1,000 LBS. 1,500 LBS	DUMP HEIGHT 10"
OPTIONS (LIST ALL THAT APPLY)	
SPECIAL CHUTE REACH (STD. 14")	
SPECIAL DUMP HEIGHT:	
SPECIAL CAPACITY:	- FRAME INVOLU
SPECIAL HOLD DOWN FINGER HEIGHT:	
SPECIAL COLOR:	
STAINLESS STEEL CHUTE***:	
FDA WHITE POWDER COAT FRAME:	
"STEEL IT" PAINT FRAME:	- 1
5-GALLON PAIL ADAPTOR FINGERS:	
*** 304 SS MILL FINISH STANDARD. PLEASE SPECIFY IF A DIFFERENT FINISH IS REQUIRED.	
POWER (150V, 1 PHASE STANDARD) IF CUSTOM, INDICATE BELOW	
	SINGLE PHASE THREE PHASE
12V D/C (115V ON-BOARD BATTERY CHARGER INCLUDED)	DECIDED CONTINUE AIR / LIVER AUT TO (45 OF M © 100 POL 1/4 ORM)
•	RECIPROCATING AIR / HYDRAULIC (15 CFM @ 100 PSI, 1/4 GPM)
CONTROLS: HAND FOOT AUTOMATED	
POWER UNIT: EXTERNAL INTERNAL (STANDARD)	
IF EXTERNAL, LENGTH OF CORDS (8' STD): IF ANY OTHER SPECIAL POWER OR	
CONTROLS ARE REQUIRED, PLEASE INDICATE:	
APPLICATION INFORMATION	
DUTY CYCLE: DUMPS PER HOUR: HOURS	PER SHIFT:
SHIFTS PER DAY: DAYS DUTY CYCLE IS CALCULATED BY STARTS PER HOUR OR NUMBER OF TIMES "UP" B	
SPECIAL TEMPERATURE REQUIREMENTS:	
ARE THERE OVERHEAD HEIGHT RESTRICTIONS?	
IS THIS A HAZARDOUS LOCATION? IF YES: CLASS:	DIV: GROUP:
OTHER SPECIAL REQUESTS OR APPLICATION INFORMATION:	